



German metal Surface treatment Chemicals Co.
Research and Development Department.
Water treatment Division.

MATERIAL SAFETY DATA SHEET

CMC 3396

MANUFACTURER:

German metal surface treatment (SUGEST)

P.O. Box 2951,Riyadh 11461,K.S.A.

Tel: (00966) (01) 4647711 (20 Lines)

Fax: (00966) (01) 2170866

1. Product and Company Identification

NAME CMC 3396
USE used as a biocide in industry
LABEL CMC 3396
Company German metal surface treatment chemicals co.

2. Product Description

CMC 3396 is a biocide in industry circulation cooling water system, wastewater treatment and swimming pool water based on isothiazoline in liquid form kill by inhibiting microbial respiration and food transport through the cell wall.

3. Hazards Identification

Emergency Overview

CAUTION!

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

May be harmful if swallowed. Slightly irritating to the eyes. Do not ingest. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Contains material that can cause target organ damage. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

Potential Health Effects

HMIS: Health 3 Flammability 0 Reactivity 0 Personal Protection: B
 4 = extreme 3 = high 2 = moderate 1 = slight

- **Inhalation:** No known significant effects or critical hazards.
- **Skin contact:** irritation occurs and corrosive promoter. Do not use undiluted on skin.
- **Eye contact:** irritating to the eyes. Damage particularly on mucous membranes of eyes. Avoid contact with eyes.
- **Ingestion:** Harmful if swallowed, may cause irritation to mouth, throat and stomach.
- **Chronic effects:** Contains material that can cause target organ damage.



Corrosion/Irritation



German metal Surface treatment Chemicals Co.
Research and Development Department.
Water treatment Division.

- **Mutagenic effects:** Mutagenic for mammalian somatic cells. [Benzalkonium chloride]. Mutagenic for bacteria and/or yeast.

4. Chemical Composition

Ingredient	CAS No	Percent
Isothiazoline	26172 – 55 - 4	10 - 30
Benzotriazole	95 – 14 - 7	1 - 10
Water	7732 – 18 - 5	To 100

5. Physical and Chemical Properties

Appearance	Clear Yellowish Colour liquid
Odour	Characteristic
pH at 25 °C	3.5 – 5.5
Density at 25 °C	1.03 ±0.04 gm/cm ³

6. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Skin contact:

Remove contaminated clothing and footwear. For skin contact, flush with large amounts of water. irritation persists seek immediate medical attention.

Eye contact:

In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and if irritation persists, seek immediate medical attention.

Ingestion:

Seek medical advice. DO NOT induce vomiting unless directed to do so by medical personnel. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having convulsions.

General advice

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep out of reach of children.



German metal Surface treatment Chemicals Co.
Research and Development Department.
Water treatment Division.

7. Fire Fighting Measures

Flammable properties not Flammable

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved..space

Hazardous thermal decomposition products : May be sulfur oxides, metal oxide/oxides, oxides of nitrogen. If heated to more than 150°C, the following substance(s) will be released: Benzyl chloride and Methyl chloride.

8. Accidental Release Measures

Use personal protection recommended in Section 10 , isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not flush into surface water or sanitary sewer system.

Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large Spill:

Corrosive liquid. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.

Clean-up methods:

Eliminate all ignition sources. Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labeled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills in original containers for re-use.

9. Handling and Storage

Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing mists or aerosols of this product. Provide adequate ventilation. Wash hands before eating, drinking, smoking, or using toilet facilities. Wash thoroughly after work using soap and water.

KEEP OUT OF REACH OF CHILDREN AND PETS. Use only as directed.

Keep away from heat and sources of ignition.

Storage:

Store in a cool, dry, well-ventilated area. Keep containers tightly closed when not in use.

Storage Conditions: Store in a cool, dry and good ventilated place. Keep container tightly closed after opening. Prevent direct sun light or ignition sources.

Temperature Limit: max 35 °C.

Maximum Storage Period: 24 Months under standard storage conditions.

Keep away from heat, open flames or other sources of ignition.

Container Type Packaging must comply with requirements of Hazardous Substances (Packaging) Regulations 2001.

For information on product shelf life, please review labels on container.

10. Exposure Controls/Personal Protection

Hazardous components



German metal Surface treatment Chemicals Co.
Research and Development Department.
Water treatment Division.

Benzotriazole	STEL: 5 (mg/m ³) [Russia] [1993] SKIN Consult local authorities for acceptable exposure limits.
Isothiazoline	TWA = 0.076 mg/m ³ STEL = 0.23 mg/m ³

Engineering controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Respiratory protection:

Use with adequate ventilation. A respirator is not needed under normal and intended conditions of product use.

Eye/face protection:

Safety glasses.

Skin protection:

For prolonged or repeated handling, use gloves. Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.

General hygiene considerations Washing with soap and water after use is recommended as good hygienic practice to prevent possible eye irritation from hand contact.

11. Stability and Reactivity

Chemical stability Stable at normal conditions.

Conditions to avoid Not available.

Incompatible materials Oxidizing agents, anionic detergents, nitrates, permanganates, silicylates, silver salts, and tartrates.

Hazardous decomposition products Thermal decomposition may yield oxides of carbon, sulfur, nitrogen and hydrogen chloride gas.

Possibility of hazardous reactions Hazardous polymerization does not occur.

12. Toxicological information

I- Isothiazoline

General Product Information

Inhalation LC50 Rat: > 13.7 mg/l

Oral LD50 Rat: 3.81 g/kg

Dermal LD50 Rabbit: >5 g/kg

Chronic Toxicity Data – A 90 day dietary study in dogs of 840 ppm of isothiazolinone resulted in no mortalities or pathological findings. A 90-day dermal study in rabbits of 0.4 mg/kg/day of isothiazolinone resulted in irritation but no pathological effects. A 30-month skin painting study with mice using 400 ppm isothiazolinone three times per week showed no increased tumor frequency over control. A teratology study with rabbits and rats was negative using dosages of 1.5 to 15 mg/kg isothiazolinone. Mutagenicity results have been equivocal.

Other Toxicological Information

May cause sensitization by skin contact. A guinea pig (Buehler technique) sensitization study with an induction dosage of 90 ppm of isothiazolinone followed by an insult of 429 ppm of isothiazolinone was positive.

II- Benzotriazole

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 500 mg/kg [Guinea pig]. Acute dermal toxicity (LD50): >1000 mg/kg [Rat]. Acute toxicity of the dust (LC50): 1910 mg/m³ 3 hours [Rat].

Special Remarks on Toxicity to Animals:

Lowest Published Lethal Dose: LDL [Rabbit] - Route: Skin; Dose 450 mg/kg



German metal Surface treatment Chemicals Co.
Research and Development Department.
Water treatment Division.

Ecotoxicity :

Aquatic Toxicity

Component #1 (CAS No.)

Test & Species Conditions

6 D LC50 rainbow trout 12.3 mg/l

96 Hr LC50 bluegill sunfish 18.7 mg/l

96 Hr LC50 goldfish

30 min EC50 Photobacterium

phosphoreum

48 Hr LC50 Daphnia magna ~ 10.6 mg/l

Component #2 (CAS No.)

Test & Species Conditions

48 Hr LC50 bluegill

Environmental Fate

This product and possible degradation products are not considered to be environmentally persistent or toxic.

13. Disposal Considerations

Disposal method:

Industrial setting: Disposal is according to all federal , state and local authorities for restrictions on disposal of chemical waste ,manage chemical, waste through an approved waste treatment facility , do not reuse empty container in accordance with current local community codes please recycle empty container whenever possible.

Waste from residues: EWC-code:

07 05 07

07 06 07

14. Transport information

DOT Classification: Class 8: Corrosive material

Land, Sea IMDG (Marine Transport) , IATA/ICAO (Air) Transport

UN Number: 3265

Shipping Name: CMC 3395

Packing Group: III



Corrosion/Irritation

15. Other Information

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

WHMIS (Canada):

CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC). CLASS D-2B: Material causing other toxic effects (TOXIC). CLASS E: Corrosive liquid.

DSCL (EEC):

REGULATORY INFORMATION

OP 07.3 F04 R1



German metal Surface treatment Chemicals Co.
Research and Development Department.
Water treatment Division.

Contains:

Corrosive Dangerous for the environment

R21/22 Harmful in contact with skin and if swallowed.

R34 Causes burns.

R50 Very toxic to aquatic organisms.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

As a general rule, persons under 18 years of age are not allowed to work with this product.

Users must be carefully instructed in the proper work procedure, the dangerous properties of the product and the necessary safety instructions.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (S.I 2002 No. 1689) with amendments.

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

EH40/2005, Workplace exposure limits 2005

The Management of Health and Safety at Work Regulations 1999 (SI 1999 No. 3242).

The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

16. Packing

HDPE container and sealed cap

DISCLAIMER: *The data contained herein are furnished for information only and are believed to be reliable. However, SUGEST and its affiliates ("SUGEST") does not assume responsibility for any results obtained by persons over whose methods SUGEST has no control. It is the user's responsibility to determine the suitability of SUGEST's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any SUGEST's products. In light of the foregoing, SUGEST specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SUGEST's products. SUGEST further disclaims any liability for consequential or incidental damages of any kind, including lost profits.*